

RE-ADVERTISEMENT

04 SEPTEMBER 2017

QUOTATIONS ARE HEREBY REQUESTED IN ACCORDANCE WITH THE SCM REGULATIONS SECTION 18 OF THE LOCAL GOVERNMENT MUNICIPAL FINANCE ACT 56 OF 2003, FOR THE PURCHASE OF ITEM/S THAT COULD BE ABOVE R30 000.00.

QUOTATIONS MUST BE SUBMITTED IN SEALED ENVELOPES CLEARLY MARKED “**SUPPLY AND DELIVERY OF HYDRAULIC TOOLS**”.

TO THE QUOTATION BOX SITUATED AT: RATES AND TAXES HALL (LESEDI OFFICES)
C/O LOUW AND HF VERWOERD STREET
HEIDELBERG
1438

ALL ENQUIRIES SHOULD BE REFERRED TO MR CLEMENT MASINGE@082 564 6817 OR TO MS SIBULELO NXATHI@016 492 0202 TO THE BIDDING PROCEDURE.

DEPARTMENT: COMMUNITY SERVICES
CLOSING DATE: 12 SEPTEMBER 2017@12H00

WORK DESCRIPTION: SUPPLY AND DELIVERY OF HYDRAULIC TOOLS:

JAWS OF LIFE

Pump / Motor Specs

Working pressure 720 bar
Type 3 stage axial
Output 1st stage (0-150 bar) 2 x 2800 cc/min
Output 2nd stage (150-280 bar) 2 x 1250 cc/min

Output 3rd stage (280 – 720 bar) 2 x 525 cc/min
Oil capacity 4000 cc
Petrol, 4 stroke, 3.0 HP/2.2kW
1700 cc fuel tank, 3 hours continuous operation
Temp range -20° to +55° C
Must have hydraulic oil level indicator
2 simultaneous tool operation
81 dB(A) sound emission unloaded.
Single hydraulic hose line
Maximum weight 24kg

Combi tool

Equipped with core tech.
Working pressure 720 bar
Spreading distance 360 mm
Max spreading force 380 kN
Max squeezing force 76 kN
Max pulling distance 416 mm



SUPPLY CHAIN MANAGEMENT UNIT

Office of the Chief Financial Officer

Max pulling force 51kN
Weight 14,2 kg
787 x 270 x 202 mm dimensions
-20°C to 55°C temp range
Required oil contents 83 cc (effective)
Handle must have integrated lighting and i-Bolt central construction

Ram

Equipped with core tech
Max working pressure 720 bar
Max spreading force 161 kN
Max pulling force 49.5 kN
Number of plungers 2
Spreading / Pulling stroke 340 (2x) mm
Required oil contents 1058 cc effective
Ready for use weight of 18.3 kg
Temp range -20 to 80°C
Dimensions of 945 x 122 x 338 mm
Retracted length 945 mm
Max length 1625 mm
Round bar of 41 mm
Must have deadman's handle of 1000 – 6000 cycles while arms are loaded.

Hoses

Max working pressure 720 bar
Max working pressure return hose 25 bar
Temp reach -20 to 80°C
Safety factor core extension hoses 4:1 (2880 bar for high pressure inner hose)
Must have bend restrictors on both sides
Two different colour coding (orange & Blue)

Name of Company: _____

Fax: _____

Telephone: _____

Date: _____

The following documents must be submitted with the quotation, failure in submitting these documents will result in a quotation being disqualified:

- Original tax clearance certificate/Tax pin from Sars
- Forms listed below (MBD 2, MBD 4, MBD 6.1, MBD 8 and MBD 9 & Clearance certificate for water & lights)
- Latest municipal account (Up to date)
- CSD registration

Bidders who did not submit an original or certified copy of their BBBEE Certificate will not be allocated preference points and will only be evaluated on price.



SUPPLY CHAIN MANAGEMENT UNIT

Office of the Chief Financial Officer

Evaluation Criteria: 80/20 Preference point system as presented in the Preferential Procurement Policy Framework Act no 5 of 2000, for this purpose MBD 2, MBD 4, MBD 6.1 MBD 8, MBD 9 and the Clearance certificate for water & lights can be downloaded on our website on the following link: www.lesedilm.gov.za/key/scm. MBD forms should be scrutinized, completed and submitted together with your quotation. All objections and complaints must be lodged within 14 days and in writing to the municipal's manager's office.

All bidders must ensure that they are registered on the National Treasury Central Supplier Database via the following link: business.support@csd.gov.za. No business will be conducted with any person who is not registered on this database.

BIDDERS ARE WELCOMED TO ATTEND THE OPENING.